

EM 6/8/10 Multi-Profile Seamless Siding Machine



When you need more options, use the EM 6/8/10 Multi-Profile Seamless Siding Machine for the job. Make multiple profiles and widths with the standard machine package, and purchase additional attachments for even more flexibility with the same machine. This machine features our self-contained embossing system that applies a natural woodgrain texture to the finished siding, adding strength and beauty.

HORIZONTAL 6-, 8-, & 10-INCH PROFILES (included with the machine)

T1-11

Horizontal 6", 8", and 10"

OPTIONAL PROFILE ATTACHMENTS

Double 3", 4", and 5"

Colonial Dutch 4" and 5"

Inverted Board and Batten 5"

011

Plank 6" and 8"

Double Dutch 4" and 5"

Beaded Horizontal 6", 8", and 10"

Half Board and Batten 4" and 5"

Dutch Lap 6", 8", and 10"

Beaded Dutch 6", 8", and 10"

► FEATURES

- · Heavy-duty steel frame for structural stability and forming consistency
- · Quick and easy profile conversion
- Industrial nitrocarburized rollers
- · Chrome-plated shafts
- · Factory-sealed bearings
- Fully driven forming stations
- · Weep hole and nail slot punches
- · Extendable cutting table
- 5-year warranty*
- · Operational training and technical support

► ADD-ON OPTIONS

- Manual guillotine, gearbox, or hydraulic shear/cutter
- · Emergency shut-off
- · Spool brake
- · Variable speed frequency drive
- · Push button control with tethered remote control and 10 ft cord
- · 6 adjustable run-out stands
- 10 run-out rails
- · Cradle with 3 coil spools
- Horner ATM control
- ► SPECIFICATIONS (as shown in photo) DIMENSIONS: 138 in. (L) x 33.5 in. (W) x 45 in. (H)

WEIGHT:

2,975 lbs

COIL WIDTHS:

9 5/64 in., 10 5/8 in., or 13 1/4 in.

MATERIALS:

Steel: 26-29 ga, Smooth or Embossed **POWER:**

1.5 HP, 110 V, Single Phase, 20 amps

OPERATIONAL SPEED:

Variable to 60 ft/min

FORMING STATIONS: 9


SHEAR/CUTTER:

Manual Guillotine

PROFILE ATTACHMENT: Double 3-, 4-, and 5-inch

MADE IN JSA

EASTSIDE MACHINE COMPANY • SALES, SERVICE, AND SUPPORT 845 34th St N, Fargo, ND 58102 • (800) 234-7834 • (701) 237-5952 • FAX (701) 232-6666 customer.service@eastsidemachine.com · www.eastsidemachine.com





TRAILER & COIL LOADING SYSTEM

ENCLOSED TRAILER 16 FT TANDEM AXLE

This enclosed trailer includes an 8-foot interior light, two 110-volt interior receptacles, a two-circuit panel with lifeline for a 110 volt, one heavy-duty aluminum access ladder, and a 14-foot ladder rack and cat walk.



COIL LOADING SYSTEM NO FORKLIFT REQUIRED

Easily load coil without using a forklift. This cradle mounts to our EM 6/8/10 Multi-Profile Seamless Siding Machine and features a powerful 110-volt electric winch.



MADE IN USA

EASTSIDE MACHINE COMPANY • SALES, SERVICE, AND SUPPORT 845 34th St N, Fargo, ND 58102 • (800) 234-7834 • (701) 237-5952 • FAX (701) 232-6666 customer.service@eastsidemachine.com • www.eastsidemachine.com

► TRAILER FEATURES

- Tandem 5,500 lb torsion axles (11,000 lb GVWR) 8-bolt hubs, 235R85/16E tires
- All-wheel electric brakes and breakaway kit
- 16 in. on-center construction,
 2 in. (H) x 6 in. (W) box frame
- Adjustable tongue
- · 24 in. tall aluminum tread plate
- Front stone guard
- · 30 in. side door with camlock
- · 3/4 in. solid-core plywood floor
- · Walls lined in 3/8 in. plywood
- $\boldsymbol{\cdot}$ Insulated walls and ceiling
- Double rear swing out cargo doors (offset design)

TRAILER SPECIFICATIONS OVERALL LENGTH: 16 ft + 4 ft tongue

OVERALL HEIGHT: 8 ft INTERIOR HEIGHT: 6 ft 6 in. REAR RUN-OUT DOOR: 35 in. (W) x 20 in. (H) CURBSIDE DOOR: 3 ft (W) x 6 ft (H) EXTERIOR MATERIAL:

0.040 in. white aluminum